



APPROVED FOR OVERHEAD LIFTING

- Approved for Overhead Lifting
- 100% Forged Alloy Steel
- Quenched & Tempered
- Easily recognizable **X100 BLAZE ORANGE** powder coating which provides protection from corrosion, and enables full exposure of identification markings
- Zinc plated prior to **X100 BLAZE ORANGE** powder coating provides superior corrosion resistance
- Markings: **X100** Brand, Size, Working Load Limit, Conformity, Traceability, 45° Indicator Arrows*
- *Convenient 45° arrows aid the end user in their rigging applications (1/2" and larger)

STOCK NUMBER	SIZE	PIN DIA.	WORKING LOAD LIMIT (TONS)	DIMENSIONS (IN)									WEIGHT/PIECE (LBS)
				A	B	C	D	E	F	G	H	J	
CX10-9624	1/2"	5/8"	3.33	0.82	0.62	1.85	0.52	1.26	1.27	2.33	3.29	2.89	0.8
CX10-9625	5/8"	3/4"	5.00	1.11	0.74	2.35	0.66	1.65	1.58	2.95	4.16	4.21	1.4
CX10-9626	3/4"	7/8"	7.00	1.25	0.88	2.79	0.79	1.95	1.88	3.49	4.90	4.21	2.4
CX10-9627	7/8"	1"	9.50	1.44	1.00	3.26	0.90	2.23	2.11	4.00	5.61	4.80	3.6
CX10-9628	1"	1-1/8"	12.50	1.60	1.11	3.72	1.09	2.67	2.39	4.65	6.25	5.39	5.8
CX10-9629	1-1/8"	1-1/4"	15.00	1.83	1.28	4.26	1.16	2.87	2.64	5.17	7.10	5.98	8.0
CX10-9630	1-1/4"	1-3/8"	18.00	2.04	1.38	4.63	1.31	3.00	3.00	5.76	7.77	6.27	10.8
CX10-9631	1-3/8"	1-1/2"	21.00	2.26	1.51	5.19	1.40	3.64	3.28	6.43	8.81	7.03	14
CX10-9632	1-1/2"	1-5/8"	30.00	2.26	1.65	5.81	1.58	3.80	3.62	6.56	9.60	7.63	18.2

Ultimate Load is 5 times the Working Load Limit

