



APPROVED FOR OVERHEAD LIFTING

- Approved for Overhead Lifting
- 100% Forged Alloy Steel
- Quenched & Tempered
- Easily recognizable **X100 BLAZE ORANGE** powder coating which provides protection from corrosion, and enables full exposure of identification markings
- Zinc plated prior to **X100 BLAZE ORANGE** powder coating provides superior corrosion resistance
- Markings: **X100** Brand, Size, Working Load Limit, Conformity, Traceability, 45° Indicator Arrows*
- *Convenient 45° arrows aid the end user in their rigging applications (1/2" and larger)

STOCK NUMBER	SIZE	PIN DIA.	WORKING LOAD LIMIT (TONS)	DIMENSIONS (IN)								WEIGHT/PIECE (LBS)
				A	B	C	D	E	F	G	H	
CX10-9600	1/4"	5/16"	0.75	0.47	0.31	1.12	0.25	0.78	0.62	1.28	1.84	0.10
CX10-9601	5/16"	3/8"	1.25	0.53	0.38	1.21	0.31	0.84	0.76	1.47	2.09	0.18
CX10-9602	3/8"	7/16"	2.00	0.66	0.43	1.43	0.38	1.03	0.92	1.78	2.49	0.31
CX10-9603	7/16"	1/2"	2.66	0.75	0.49	1.68	0.44	1.16	1.07	2.03	2.91	0.49
CX10-9604	1/2"	5/8"	3.33	0.81	0.62	1.88	0.50	1.31	1.22	2.33	3.29	0.74
CX10-9605	5/8"	3/4"	5.00	1.06	0.75	2.36	0.63	1.69	1.57	2.95	4.16	1.44
CX10-9606	3/4"	7/8"	7.00	1.26	0.87	2.81	0.75	2.01	1.89	3.49	4.90	2.16
CX10-9607	7/8"	1"	9.50	1.46	0.98	3.33	0.87	2.28	2.13	4.00	5.61	3.37
CX10-9608	1"	1-1/8"	12.50	1.71	1.10	3.79	1.04	2.70	2.36	4.65	6.25	5.30
CX10-9609	1-1/8"	1-1/4"	15.00	1.89	1.26	4.29	1.14	2.95	2.68	5.17	7.10	7.40
CX10-9610	1-1/4"	1-3/8"	18.00	2.09	1.38	4.74	1.26	3.31	2.99	5.76	7.77	9.60
CX10-9611	1-3/8"	1-1/2"	21.00	2.32	1.50	5.28	1.38	3.70	3.31	6.43	8.81	13.50
CX10-9612	1-1/2"	1-5/8"	30.00	2.44	1.65	5.85	1.50	3.90	3.62	6.56	9.60	17.35

Ultimate Load is 5 times the Working Load Limit

